## 2020 KLX®110L







90mm mechanical drum, cable actuated

110mm mechanical drum, rod actuated

Backbone frame, high-tensile steel

3.00x12

24.2° / 1.9 in

61.4 in

25.6 in

39.0 in

10.4 in

28.7 in

167.5 lb\*

P	N	W	F	R
	u	v	ш	•

**Engine** 4-stroke single, SOHC, air-cooled

Displacement 112cc

**Bore x Stroke** 53.0 x 50.6mm

Compression

Ratio

9.5:1

**Fuel System** 18mm Keihin carburetor and screw type

throttle limiter on grip housing

Ignition DC-CDI

**Transmission** 4-speed, return shift, wet multi-disc

manual clutch

**Final Drive** Chain

## **PERFORMANCE**

**Front** Suspension / **Wheel Travel** 

30mm hydraulic telescopic fork/5.5 in

Rear

Swingarm with single hydraulic shock/5.2

Suspension / **Wheel Travel** 

2.50x14

**Seat Height** 

**Rear Tire** 

**Front Brakes** 

**Rear Brakes** 

**DETAILS** 

**Frame Type** 

Rake/Trail

**Overall Length** 

**Overall Width** 

**Overall Height** 

Ground

Clearance

**Curb Weight** 

**Fuel Capacity** 

Wheelbase

42.3 in

1.0 gal

**Color Choices** 

Lime Green

Warranty

6 Months

Scan with camera to view videos. key features and more.

**Front Tire** 

