²⁰²⁰ KLX[®]140G







POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	144cc
Bore x Stroke	58.0 x 54.4mm
Compression Ratio	9.5:1
Fuel System	20mm Keihin carburetor
Ignition	Digital DC-CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	4.10x18
Front Brakes	Single 220mm petal disc with a dual- piston caliper
Rear Brakes	Single 186mm petal disc with single- piston caliper

DETAILS

	Frame Type	Tube, semi-double cradle
ti-disc	Rake/Trail	27°/4.6 in
	Overall Length	78.9 in
	Overall Width	31.1 in
	Overall Height	44.7 in
	Ground Clearance	12.4 in
le shock ebound	Seat Height	33.9 in
	Curb Weight	218.2 lb*
	Fuel Capacity	1.5 gal
	Wheelbase	52.4 in
	Color Choices	Lime Green
	Warranty	6 Months

PERFORMANCE

Front Suspension / Wheel Travel	33mm telescopic fork/7.5 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with piggyback reservoir, 22-way rebound damping and threaded preload adjustability/7.9 in
Front Tire	2.75x21



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit honduras.kawasaki-la.com for full product details.