POWER







. •	
Engine	2-stroke single with exhaust power valve, liquid-cooled
Displacement	99cc
Bore x Stroke	52.5 x 45.8mm
Compression Ratio	10.2:1 (low speed) - 8.7:1 (high speed)
Fuel System	28mm Keihin carburetor
Ignition	CDI with digital advance
Transmission	6-speed, return shift, with wet multi-disc manual clutch

Rear Tire	90/100-16
Front Brakes	Single 220mm petal disc with dual-piston caliper
Rear Brakes	Single 220mm petal disc with single-piston caliper

	Rear
	DE
	Fram
	Rake
sc	Overa
	Over
	Overa
	Grou Clear

DETAILS		
Frame Type	High-tensile steel perimeter design withsubframe member	
Rake/Trail	29°/4.3 in	
Overall Length	75.6 in	
Overall Width	30.1 in	
Overall Height	45.3 in	
Ground Clearance	13.0 in	
Seat Height	34.3 in	
Curb Weight	169.7 lb*	
Fuel Capacity	1.32 gal	
Wheelbase	51.6 in	
Color Choices	Lime Green	

Not Available

PERFORMANCE

Final Drive

Front Suspension / Wheel Travel	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring preload/10.8 in

Chain

Front Tire 70/100-19





Warranty