## <sup>2020</sup> **KX<sup>™</sup>250**







## POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	249cc
Bore x Stroke	78.0 x 52.2mm
Compression Ratio	14.2:1
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors
Ignition	Digital CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	100/90-19
Front Brakes	Single semi-floating 270mm Braking® petal disc with dual-piston caliper
Rear Brakes	Single 250mm Braking® petal disc with single-piston caliper

## **DETAILS**

	Frame Type	Aluminum perimeter
	Rake/Trail	28.6°/5.1 in
	Overall Length	85.5 in
	Overall Width	32.3 in
	Overall Height	50.0 in
	Ground Clearance	13.1 in
	Seat Height	37.3 in
	Curb Weight	221.1 lb without fuel / 231.4 lb*
	Fuel Capacity	1.69 gal
<	Wheelbase	58.3 in
1	Color Choices	Lime Green
	Warranty	Not Available

## PERFORMANCE

Front Suspension / Wheel Travel	48mm inverted telescopic coil spring fork with 23-way compression damping and 20- way rebound damping/12.4 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with dual range (2 1/16 turns stepless high speed /21-way low speed) and 38-way rebound damping and adjustable spring preload/12.2 in
Front Tire	80/100-21

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit honduras.kawasaki-la.com for full product details.