## BRUTE FORCE<sup>®</sup> 750 4x4i EPS CAMO







Yes

10.5 ft

1250 lb

242.0 lb

88.0/176.0 lb

35W headlights, 5W taillight, 21W stoplight

## POWER

| Engine                   | 4-stroke, V-twin, SOHC, liquid-cooled                                   |  |
|--------------------------|---|--|
| Displacement             | 749cc   |  |
| Bore x Stroke            | 85.0 x 66.0mm   |  |
| <b>Compression Ratio</b> | 9.3:1   |  |
| Fuel System              | DFI® with two 36mm throttle bodies                                      |  |
| Ignition                 | Digital DC-CDI  |  |
| Transmission             | Automatic CVT (H,L,N,R)   |  |
| Final Drive              | Selectable 2WD/4WD with variable control front differential lock, shaft |  |

## DETAILS

**Electronic Power** 

**Towing Capacity** 

**Rack Capacity**,

Front/Rear

**Total Rack Capacity** 

Steering (EPS) Turning Radius

| ol front    | Frame Type       | Double-cradle, high-tensile tubular steel   |
|-------------|------------------|---|
|             | Track Front/Rear | 36.4/35.0 in  |
|             | Overall Length   | 86.4 in   |
|             | Overall Width    | 46.5 in   |
|             | Overall Height   | 48.0 in   |
|             | Seat Height      | 35.8 in   |
|             | Curb Weight      | 699.0 lb*   |
|             | Wheelbase        | 50.6 in   |
| n calipers  | Instruments      | Speedometer, odometer, dual trip meters, fuel gauge,  |
| endent park |                  | engine temp, clock, hour meter and 2WD/4WD icon, plus indicators for EPS, neutral, belt, and oil pressure |
|             | Color Choices    | Realtree Xtra® Green Camo   |
|             | Warranty         | 12 Month Limited Warranty   |
|             |                  |   |
|             |                  |   |

## CAPABILITY

| Front Suspension /<br>Wheel Travel | Double wishbone/6.7 in                                     |  |
|------------------------------------|--|--|
| Rear Suspension /<br>Wheel Travel  | Double wishbone/7.5 in                                     |  |
| Front Tires                        | AT 25 x 8-12   |  |
| Rear Tires                         | AT 25 x 10-12  |  |
| Front Brakes                       | Dual hydraulic 200mm discs with 2-piston calipers          |  |
| Rear Brakes                        | Sealed, oil-bathed, multi-disc with independent park brake |  |
| Ground Clearance                   | 9.4 in   |  |
| Starting System                    | Electric   |  |
| Fuel Capacity                      | 5.0 gal  |  |



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit honduras.kawasaki-la.com for full product details.