#### 2020

# **MULE**<sup>™</sup> 4000









### **POWER**

4-stroke, 2-cylinder, OHV 90° V Liquid-cooled, gas **Engine** 

617cc Displacement

**Maximum Torque** 34.7 lb-ft @ 2500 rpm

**Bore x Stroke** 2.99x2.68 in

**Compression Ratio** 

**Fuel System** DFI® with 34mm Mikuni throttle body

**Transmission** Continuously Variable Transmission (CVT) with (H,N,R)

**Final Drive** 2WD, shaft. Dual mode rear differential with

differential lock

**Engine Braking** 

**Alternator Output** 

(max)

23 amp

Rear Brakes	Drum
Ground Clearance	7.5 in
Fuel Capacity	6.3 gal
Turning Radius	11.0 ft

**Cargo Bed Dimensions** (LxWxH)

46.3 x 51.6 x 11.4 in

**Cargo Bed Load** Capacity

1327 lb

800 lb

**Payload Capacity** 

**Seating Capacity** 

**Towing Capacity** 1200 lb

Lighting

(2) Halogen headlights, (2) tail/brake lights,(2) Halogen

tail/brake lights

## **CAPABILITY**

Front Suspension /	MacPherson Strut/3.9 in
Wheel Travel	

Rear Suspension / **Wheel Travel** 

DeDion Axle/2.8 in

**Front Tires** 

23x11.00-10

23x11.00-10 **Rear Tires** 

Steering Rack-and-pinion

**Park Brake Type** 

Independent, Mechanical Drum

**Front Brakes** Drum

## **DETAILS**

Overall Length	116.7 in
Overall Width	62.0 in
Overall Height	75.8 in
Curb Weight	1338.4 lb
Wheelbase	73.6 in

Parking brake warning light, coolant temperature **Instruments** warning light, 12V DC outlet, fuel gauge, hour meter

**Wheel Type** Steel

**Color Choices** Timberline Green, Dark Royal Red

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

