MULE 4000 TRANS™









POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V, liquid-cooled, gas

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking Nο

Alternator Output 23 amp

(max)

Ground Clearance

Fuel Capacity 6.3 gal

Turning Radius 12.8 ft

Cargo Bed Dimensions (LxWxH)

Rear Brakes

50.4 x 47.6 x 11.2 in (2-person),30.3 x 47.6 x 11.2 in (4-

Drum

7.7 in

Cargo Bed Load

Capacity

800 lb (2-person),400 lb (4-person)

Payload Capacity 1330 lb

Seating Capacity 2-4

Towing Capacity 1200 lb

Lighting (2) Halogen headlights, (2) Halogen tail/brake lights

CAPABILITY

MacPherson Strut/3.9 in Front Suspension / **Wheel Travel**

Rear Suspension /

DeDion Axle/2.8 in

Wheel Travel Front Tires

23x11.00-10

Rear Tires

23x11.00-10

Park Brake Type Independent, Mechanical Drum

Electric Power Steering (EPS)

Front Brakes

Steering

Drum

DETAILS

Overall Length 128.5 in

Overall Width 58.5 in

Overall Height 78.1 in

Curb Weight 1514.1 lb*

Wheelbase 85.2 in

Parking brake warning light, coolant temperature Instruments

warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Bright White

Warrantv Kawasaki 3-Year Limited Warranty



