MULE 4000 TRANS™







Drum

7.7 in

6.3 gal

12.8 ft

1330 lb

1200 lb

2-4

POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V, liquid-cooled, gas

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking Nο

(max)

Alternator Output 23 amp

CAPABILITY

MacPherson Strut/3.9 in Front Suspension / **Wheel Travel**

Rear Suspension / **Wheel Travel**

DeDion Axle/2.8 in

Front Tires 23x11.00-10 **Rear Tires** 23x11.00-10

Steering Electric Power Steering (EPS)

Park Brake Type

Independent, Mechanical Drum

Front Brakes Drum

Overall Length 128.5 in

Rear Brakes

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

DETAILS

Cargo Bed Dimensions

(LxWxH)

Capacity

Lighting

Ground Clearance

Overall Width 58.5 in

Overall Height 78.1 in

Curb Weight 1514.1 lb*

Wheelbase 85.2 in

Parking brake warning light, coolant temperature Instruments

warning light, 12V DC outlet, fuel gauge, hour meter

50.4 x 47.6 x 11.2 in (2-person),30.3 x 47.6 x 11.2 in (4-

(2) Halogen headlights, (2) Halogen tail/brake lights

800 lb (2-person),400 lb (4-person)

Wheel Type Steel

Color Choices Bright White

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

