MULE™ 4010 4x4









POWER

4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled, gas **Engine**

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear

differential with differential lock

Engine Braking

Alternator Output 23 amp

(max)

Rear Brakes Drum **Ground Clearance** 6.9 in **Fuel Capacity** 6.3 gal

Turning Radius 11.2 ft

Cargo Bed Dimensions 46.3 x 51.6 x 11.4 in

(LxWxH)

Cargo Bed Load

Payload Capacity

Capacity

1327 lb

800 lb

Seating Capacity

Towing Capacity

1200 lb

Lighting (2) Halogen headlights,(2) tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in **Wheel Travel**

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Independent, Mechanical Drum

Front Tires 23x11.00-10 **Rear Tires** 23x11.00-10

Steering Electric Power Steering (EPS)

Front Brakes Drum **DETAILS Overall Length**

Warranty

116.7 in

Overall Width 62.0 in

Overall Height 75.8 in

Curb Weight 1432.6 lb*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices Timberline Green, Dark Royal Red

Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

Park Brake Type

