
MULE™ 4010 TRANS4x4®









POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2500 rpm

Bore x Stroke 2.99x2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear

differential with differential lock

Engine Braking No

Alternator Output 23 amp

(max)

Rear Brakes Drum

Ground Clearance 7.1 in

Fuel Capacity 6.3 gal

Turning Radius 12.8 ft

Cargo Bed Dimensions (LxWxH) 50.4 x 47.6 x 11.2 in (2-person)30.3 x 47.6 x 11.2 in (4-person)

perso

Cargo Bed Load Capacity

pacity 1330 lb

S - - 1 - - - C - - - - - 1 - -

Seating Capacity 2-4

Towing Capacity

Payload Capacity

pacity 1200 lb

Lighting (2) Halogen headlights, (2) Halogen tail/brake lights

800 lb (2-person)400 lb (4-person)

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Steering Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

DETAILS

Overall Length

128.5 in

Overall Width 58.5 in

30.5 111

Overall Height

75.8 in

Curb Weight

1586.9 lb*

Wheelbase

85.2 in

Instruments

Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Color Choices

Timberline Green, Dark Royal Red

Warranty

Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

