## **MULE PRO-DXT™ DIESEL**







## **POWER**

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2400 rpm

Bore x Stroke 2.91x3.03 in

Compression Ratio 23.5:

Fuel System Bosch in-line injection pump

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

**Alternator Output** 

(max)

55 amp

## **CAPABILITY**

Front Suspension / Double wishbone / 8.7 in Wheel Travel

Rear Suspension / Wheel Travel

**Rear Tires** 

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12

Steering Rack-and-pinion, Tilt steering

26x11.00-12

Park Brake Type Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

Ground Clearance 10.2 in

Fuel Capacity 7.9 gal
Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-

Dimensions (LxWxH)

po.55..,

1000 lb (3-person)350 lb (6-person)

Cargo Bed Load

Capacity

Payload Capacity 1581 lb

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2000 lb

Lighting (2) Halogen headlights, (2) Halogen tail/brake lights

## **DETAILS**

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1922.8 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps

Color Choices Super Black

Warranty Kawasaki 3-Year Limited Warranty



