## **MULE PRO-DXT™ EPS DIESEL**









## **POWER**

**Engine** 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

**Maximum Torque** 38.3 lb-ft @ 2400 rpm

**Bore x Stroke** 2.91x3.03 in

**Compression Ratio** 

**Fuel System** 

**Transmission** Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

**Engine Braking** 

**Alternator Output** 

Bosch in-line injection pump

with differential lock

(max)

55 amp

## **CAPABILITY**

Front Suspension / **Wheel Travel** 

Double wishbone/8.7 in

Rear Suspension / **Wheel Travel** 

Double wishbone/8.5 (L) /8.7 (R) in

**Front Tires** 26x9.00-12

**Rear Tires** 26x11.00-12

Steering Electric Power Steering (EPS), Tilt steering

**Park Brake Type** Independent, Mechanical Disc

**Front Brakes** Dual Disc, 2 piston caliper

**Rear Brakes** Dual Disc, 1 piston caliper **Ground Clearance** 10.2 in

**Fuel Capacity** 7.9 gal 16.0 ft

**Turning Radius** 

**Cargo Bed Dimensions** (LxWxH)

42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-

1000 lb (3-person)350 lb (6-person)

**Cargo Bed Load** 

Capacity

**Payload Capacity** 1581 lb

**Seating Capacity** 3-person (1 row), 6 person (2 row)

**Towing Capacity** 

Lighting (2) Halogen headlights, (2) Halogen tail/brake lights

## **DETAILS**

**Overall Length** 133.3 in

**Overall Width** 64.0 in

**Overall Height** 77.6 in

1936.0 lb\* **Curb Weight** 

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder

**Color Choices** Timberline Green, Bright White

Warranty Kawasaki 3-Year Limited Warranty



