2020

MULE SX™









POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled, gas

Displacement 401cc

Maximum Torque 20.6 lb-ft @ 2200 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio 8.3:1

Fuel System Nikki 6C1026 carburetor

Transmission Continuously Variable Transmission (CVT) with (H,N,R)

Final Drive 2WD, shaft. Dual mode rear differential with

differential lock

Engine Braking No

Alternator Output 17 amp

(max)

Rear Brakes Drum **Ground Clearance** 6.1 in **Fuel Capacity** 4.2 gal

Turning Radius 10.8 ft

Cargo Bed Dimensions (LxWxH)

35.6 x 40.9 x 9.6 in

Cargo Bed Load

Capacity

DETAILS

Overall Length

Overall Width

Overall Height

Curb Weight

Wheelbase

Instruments

400 lb

106.7 in

52.6 in

70.1 in

70.1 in

967.6 lb**

Payload Capacity 926 lb

Seating Capacity

1100 lb* **Towing Capacity**

Lighting (2) Halogen headlights,(2) Halogen tail/brake lights

CAPABILITY

MacPherson Strut/3.1 in Front Suspension / **Wheel Travel**

Rear Suspension / **Wheel Travel**

Unit Swingarm/3.1 in

Front Tires

22x9.00-10 **Rear Tires** 22x11.00-10

Steering Rack-and-pinion

Park Brake Type

Independent, Mechanical Drum

Front Brakes Drum **Color Choices**

Fuel gauge, hour meter, oil temp light, parking brake

Timberline Green, Dark Royal Red

Warranty

Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



*Requires Optional Hitch