MULE SX™ 4x4 FI









35.6 x 40.9 x 9.6 in

915 lb

POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2400 rpm

Bore x Stroke 3.23x2.99 in

Compression Ratio 8.6:1

Fuel System Fuel injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking No

Alternator Output 22.9 amp

(max)

r

CAPABILITY

Front Suspension / MacPherson Strut/3.1 in Wheel Travel

Rear Suspension / Unit Swingarm/3.1 in

Wheel Travel

Front Tires 24x9.00-10

Rear Tires 24x11.00-10

Steering Rack-and-pinion, Tilt steering

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

Rear Brakes Drum

Ground Clearance 6.7 in

Fuel Capacity 4.2 gal

Turning Radius 10.8 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load 400 lb

Capacity

Payload Capacity

.

Seating Capacity 2

Towing Capacity 1100 lb*

Lighting (2) Halogen headlights, (2) Halogen tail/brake lights

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 70.9 in

Curb Weight 1031.9 lb**

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

light

Wheel Type Steel

Color Choices Timberline Green, Dark Royal Red

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

